

Atty. Docket No.: 1050.P001US

10/057,604

**WHAT IS CLAIMED IS:**

1. (Currently Amended) A device for carrying a large object, comprising:  
a continuous cradle operable to support the carried large object;  
at least one carrying strap attached to opposing ends of the cradle, the at least one carrying strap forming a single lifting point; and  
at least one restraining strap attached to the at least one carrying strap, the at least one restraining strap restraining the sides of the large object not restrained by the carrying strap when the carrying strap is used to carry the large object.
2. (Previously Presented) The device in claim 1, wherein a plurality of carrying straps are detachably gathered by a handle operable to form a single lifting point.
3. (Previously Presented) The device in claim 2, wherein the continuous cradle comprises a pliable material operable to substantially distribute support of the object along a bottom surface of the object.
4. (Previously Presented) The device in claim 2, further comprising a means for adjusting the length of the at least one carrying strap.
5. (Previously Presented) The device in claim 2, further comprising a means for adjusting the length of the at least one restraining strap.
6. (Previously Presented) The device in claim 2, wherein the restraining straps number two or more, one of the straps located near the continuous cradle.
7. (Previously Presented) The device in claim 2, wherein the device, when empty, folds into a compact configuration for portability.
8. (Previously Presented) A method for carrying an object, comprising the steps of:  
substantially cradling a bottom surface of the object within a continuous cradle;  
attaching at least one carrying strap to opposing ends of the continuous cradle;

Atty. Docket No.: 1050.P001US

10/057,604

extending the at least one carrying strap up opposing sides of the object to form a single lifting point; and

attaching at least one restraining strap to the at least one carrying strap to restrain the sides of the object not restrained by the carrying strap.

9. (Previously Presented) The method in claim 8, wherein a plurality of carrying straps are detachably joined with a handle operable to form the single lifting point.

10. (Original) The method in claim 8, further comprising the step of adjusting the length of the carrying strap.

11. (Original) The method in claim 8, further comprising the step of adjusting the length of the restraining strap.

12. (Previously Presented) The method in claim 8, further comprising the step of attaching a restraining strap to the continuous cradle.

13. (Previously Presented) The method in claim 8, further comprising the step of folding the continuous cradle, the carrying strap and the restraining strap into a compact configuration for portability.

14. (Previously Presented) A system for carrying an object, the system comprising:  
a continuous cradle;  
at least one carrying strap attached to opposing ends of the continuous cradle and joined to form a single lifting point; and  
a plurality of restraining straps attached to the at least one carrying strap and acting to restrain the objects within the continuous cradle.

15. (Previously Presented) The system in claim 14, wherein a plurality of carrying straps are detachably joined with a handle operable to form a single lifting point.

Atty. Docket No.: 1050.P001US

10/057,604

16. (Previously Presented) The system in claim 14, wherein the continuous cradle comprises a pliable material operable to substantially distribute support of the object along a bottom surface of the object.

17. (Original) The system in claim 14, further comprising a means for adjusting the length of the at least one carrying strap.

18. (Original) The system in claim 14, further comprising a means for adjusting the length of the at least one restraining strap.

19. (Previously Presented) The system in claim 14, wherein one of the restraining straps is located near the continuous cradle.

20. (Original) The system in claim 14, wherein the device, when empty, folds into a compact configuration for portability.